



VACUUM CLEANERS - SPECIAL SOLUTIONS - FLOODED AREA EMPTYING

GS 2/62 SUB

NEW

POWER MAX

2400 W

WATER LIFT

2470 mmH₂O

AIRFLOW

420 m³/h

TANK CAPACITY

62 l



EXCLUSIVE CHARACTERISTICS

- ▶ AP TUBE
- ▶ INNOVATIVE GASKET
- ▶ STRONG HOOKS
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ SUBMERSIBLE PUMP
- ▶ DOUBLE STAGE MOTORS

MOST FREQUENTLY USE

AGRICULTURE



CONSTRUCTION



HARDWARE CUSTOMER



HEAVY INDUSTRY



AUTOMOTIVE



INNOVATIONS



SPECS



PROFESSIONAL SUBMERSIBLE PUMP



INTEGRATED ANTI-FOAM SYSTEM



ELECTRIC POWER SOCKET ON BOARD

TECHNICAL DATA

		GS 2/62 SUB
Code		ASD015119
PERFORMANCE		
Usage		WET & DRY
Motor		2x2 stage
Power	W	2400 max
Voltage	V	220-240
Water lift	mmH ₂ O	2470
Airflow	m ³ /h	420
Tank Capacity/Material	l	62/steel
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	74
Pump type		Plastic
Pump power	W	370
Pump capacity	l/min	180
Delivery head	m	7
Diameter of accessories	mm	38
Dimensions (LxWxH)	mm	550x600x960
Weight	kg	21,0

STANDARD EQUIPMENT

PMDT00350 ACCESSORIES KIT FOR SUB Ø38 MM COMPOSED OF:

CODE: TBFX28237
FLEXIBLE HOSE 2,5 M



CODE: LAFN43048
ALUMINIUM/PLASTIC
TUBES 2X50 CM



CODE: MPVR43047
HANDLE WITH AIR
REGULATOR



CODE: SPPV43051
WET TOOL



IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com

